



Decorscreed

Decorative Industrial Floor Screed

USES

DECORSCREED is a blend of solvent free epoxy resins, curing agents and graded coloured quartz aggregates. The components of the product have been carefully selected to provide Decorscreed with excellent application properties.

DESCRIPTION

DECORSCREED provides a hard wearing, impact and abrasion resistant decorative floor surface. The product has been designed for use in a wide range of industrial and commercial environments such as pharmaceutical, food and beverage, packing and light manufacturing, hospitals, reception areas, laboratories, retail premises and custodial buildings.

ADVANTAGES

Durable	Hard wearing surface resistant to both impact damage and abrasion
Seamless	Provides a joint-free, easy to clean surface
Slip Resistant	lightly textured profile provides a good non slip surface to pedestrian traffic
Decorative	Attractive multi-coloured floor system
Thickness	4-5mm giving no interference with existing levels
Low odour	Non tainting and suitable for use in sensitive areas

SLIP RESISTANCE

Slip Resistance Value – BS 7976-2 : 2002

4S Rubber Slider Wet	46
4S Rubber Slider Dry	59
TRL Rubber Wet	50
TRL Rubber Dry	94

CHEMICAL RESISTANCE

DECORSCREED is resistant to a wide range of chemicals. Specific data is available on request from the Technical Services Department.



TEMPERATURE

DECORSCREED should not be applied at temperatures below 10° C and above 40° C. A combination of low temperature and high humidity can effect the application and curing of this product.

COLOURS

DECORSCREED is available in a range of blended colours, offering the designer a wide choice, subject to status. Contact our Technical Services Department for details.

INSTRUCTIONS FOR USE

SURFACE PREPARATION - CONCRETE

It is essential that the substrate surfaces are correctly prepared prior to application. New concrete or cementitious substrates should have been placed for at least 28 days, unless specially water reduced and give a protimeter reading of less than 75% RH before applying the Decorscreed system. All substrates should be sound and free from contamination with oil, grease and other matter. Any oil or grease contamination must be removed completely by grinding, scabbling or shotblasting the contaminated areas to provide a clean substrate. It may be possible to prepare lightly contaminated areas by treatment with XD80 Degreaser (please refer to Technical Services Department). Laitance should be removed by vacuum blasting, grinding or light scabbling. Old concrete floors should be prepared by one of the mechanical methods mentioned above. Ensure that all concrete substrates are free from rising damp.

PRECAUTIONS

DECORSCREED is a non-flammable product. Decorscreed should not be allowed to come into contact with skin and eyes or be swallowed. Epoxy resins and hardeners may act as skin sensitizers to some people. Gloves, goggles and a suitable barrier cream should therefore be used. Ensure adequate ventilation if working in enclosed areas. Skin contamination with any of the products should be removed immediately with soap and water. In the event that mixed resin comes into contact with the skin, it must be removed before it hardens with a good quality resin removing cream, followed by washing with soap and water. Do not use solvent. If accidental eye contamination occurs irrigate with copious quantities of clean water and seek medical advice. If ingestion of any of the materials takes place, seek medical attention immediately. Do not induce vomiting.

DISPOSAL

All tools and equipment should be cleaned with Conren Solvent Cleaner immediately after use. Spillage should be absorbed with sand or sawdust and disposed of in accordance with statutory regulations.

STORAGE

Shelf life at least 12 months if stored in original containers between 10° C and 25° C.

CONTRACTING SERVICE

Conren Limited offers a contracting service for the application of all Conren products. This facility is back by a comprehensive technical and after sales service. We are able to contend with most problems in the field.


TECHNICAL SERVICE & QUALITY ASSURANCE

All information provided in this leaflet is based on results obtained from our own experience and test and is given in good faith. The user will be deemed to have satisfied himself independently of the suitability of Conren's products for his own particular purpose. We guarantee to replace, free of charge, any goods supplied by us which are proved to our satisfaction defective, but, as the application of these materials is necessarily beyond our control, we will not accept responsibility for any damage or loss arising wholly or in part from these materials. Except as herein provided, any express or implied condition, warranty, statement or representation, statutory or otherwise as to the quality of the goods is expressly excluded.

DECORSCREED STANDARD COLOURS



SMOKE



CORN



RUSSET




BRICK



FOREST



LAWN



MIDNIGHT



SKY

SPECIFICATION

Decorative epoxy quartz screed shall be Conren Decorscreed.
All products to be applied in accordance with Conren's written instructions.

Conren Limited
Ditton Road
Widnes
Cheshire
WA8 0PG
UK

Tel: +44 (0) 151 422 3999
Fax: + 44 (0) 151 424 5053
e-mail: info@conren.com
web: www.conren.com